



Haltdos Remote Access Gateway Techspecs

Base Models	HD-RAG-1100	HD-RAG-4100	HD-RAG-4600	HD-RAG-5100	HD-RAG-5400	HD-RAG-6200
MITIGATION PERFORMANCE						
L4 Throughput	upto 1 Gbps	upto 5 Gbps	upto 24 Gbps	upto 48 Gbps	upto 72 Gbps	upto 120 Gbps
L7 Throughput	upto 1 Gbps	upto 4 Gbps	upto 20 Gbps	upto 40 Gbps	upto 60 Gbps	upto 100 Gbps
SSL Throughput	1 Gbps	4 Gbps	20 Gbps	40 Gbps	50 Gbps	100 Gbps
Compression Throughput	1 Gbps	4 Gbps	20 Gbps	48 Gbps	48 Gbps	96 Gbps
Decompression Throughput	1 Gbps	5 Gbps	20 Gbps	60 Gbps	60 Gbps	120 Gbps
SSL/TLS Connections per Second	10K (RSA 2K) 5K (ECC)	22K (RSA 2K) 15K (ECC)	40K (RSA 2K) 25K (ECC)	95K (RSA 2K) 48K (ECC)	95K (RSA 2K) 48K (ECC)	190K (RSA 2K) 96K (ECC)
Max Concurrent Connections	7 M	16 M	24 M	56 M	96 M	160 M
HARDWARE SPECS						
Processor	Intel Xeon	Intel Xeon	Intel Xeon	Intel Xeon	Intel Xeon	Intel Xeon
CPU Cores	8	8	20	32	40	64
Minimum Memory	12 GB	16 GB	32 GB	64 GB	128 GB	256 GB
Minimum Hard Disk	128 GB SSD	256 GB SSD	256 GB SSD	512 GB SSD	1 TB SSD	2 TB SSD
	Option available for RAID or dual partition					
Additional Specs	Built-in TPM Chip and Hardware HSM for SSL offloading & compression optimization Option available for FIPS-140-2 (additional charge) or Non-FIPS compliant HSM					
Form Factor	1U/2U Rack Mount Server (19 inch mounting) with panel indicators					
Power Supply	Redundant Power Supply (Hot Swappable) AC 170-240V, 50 Hz					
Operating Temperature	0° –40° C					
Humidity	8% - 95% (non-condensing)					
INSPECTION PORTS						
1 GE Ports	4	8	8	-	-	-
10 GE Ports	-	-	2	4	8	8
25 GE Ports	-	-	-	-	-	-
40 GE Ports	-	-	-	2	2	4
100 GE Ports	-	-	-	-	-	-
No. of ports can be customized over the base model						
OUT OF BAND PORTS						
1 GE (RJ-45) Ports	2	2	2	2	2	2
Console (RS232/RJ45) Ports	1	1	1	1	1	1
HA Ports (RJ-45/SFP/SFP+)	1	1	1	1	1	1
Input/Output (USB)	2	2	2	2	2	2
TECHNOLOGY, CERTIFICATION & SUPPORT						
Platform	Haltdos Platform – hdPlatform (EAL 2+ Certified)					
License	Unlimited users. Bandwidth capping on provided license. Upgrade possible without hardware replacement upto max supported bandwidth on hardware. Concurrent users capping based on bandwidth utilization as per license.					
Certification	FCC, ROHS, CE compliant, Common Criteria EAL 2+					
Support	24x7 Support with dedicated Account Manager					
Warranty	1 year software and hardware maintenance. Additional changes for extended warranty					
TAC Support	TACsupport in India					
HIGH AVAILABILITY						
Multiple Appliances	N+1 Active -Active or Active –Passive (VRRP)					
Management Modes	Standalone / Centralized Management (VM or appliance) with Haltdos Hawk					
Secure Communication	Secure communication between centralized management and HA appliances for state synchronization					
INTEGRATION FEATURES						
Storage and Export	Local retention of logs, reports and events. Support for export to 3 rd party storage					
NIMS Integration	Support for SNMP, NTP / SNTP, DNS, Web Proxy integration					
Notification Integration	Notification & Logging via SNMP, SMTP, SMS Gateway and 3 rd party integration via API hooks					
SIEM Integration	Support for integration with SIEM and Syslog services					
AAA Integration	Support for integration via RADIUS and TACACS+					
Identity Management	Inbuilt with support for integration with AD / SAML/ LDAP					
MANAGEMENT FEATURES						
Graphical User Interface (GUI)	Secure web interface over HTTPS with support for all modern browsers					
Command Line Interface (CLI)	Command Line Interface over SSH or console port					
API Integration	Yes (XML or JSON) via SDK					
Logging	Centralized logging of system, services, MIS, incidents					
Dashboards	Real-Time & historical dashboards with custom duration. Support for custom dashboards					
System Status Dashboard	Status dashboard for 1-click health check					
Reporting	Periodic daily, weekly or monthly reports in PDF or Excel					
RBAC Administration	Configurable user profiles with role based access control					
Backup	Automatic or manual backup and restore					
Policy Management	On the fly configuration updates on mitigation appliances					
Certificate Management	SSL certificate management with support for Let's Encrypt certificate generation					
Events / Alerts	Detailed event and alert reporting on attack, health, etc.					
Updates	Update and upgrade management on version releases and patch updates from Haltdos					
Audit Rule	Generates a report on the configuration settings to ensure compliance with predefined standards					
VPN FEATURES						
HTTP Protocols	Supports HTTP 0.9/1.0/1.1/2.0 with translation					
SSL/TLS Management	Includes support for SSL v2/v3, TLS 1.0/1.1/1.2/1.3 with offloading and re-encryption using custom cipher suites. Offers client certificate-based authentication and proxy SSL/TLS connections					
Dynamic Routing Protocols	Supports BGP, OSPF, RIP v1, and RIP v2					
Networking	Includes VLAN, Link Aggregation, and Trunking (LACP) support					
Client Support	Provides access for Windows, Linux, Mobile Apps (Android and iOS), and Web (via browser-based solutions, ActiveX & Java Applet)					
Authentication	Supports Password, SAML, AD/LDAP, SSO, AAA, OAuth, Step-up Authentication and third-party integrations via Webhooks					
NAT & Routing	Enables client, server, or full NAT and static routing for IPv4 and IPv6					
Concurrent User / Scalability	Scalable architecture supporting expansion to 4000+ concurrent users through vertical/horizontal scaling.					

User Grouping	Allows creation of multiple users and user groups with granular access control
Clientless Access	Offers secure resource access via web browsers without additional client installation
Granular Access Control	Configurable policies to control user access to specific resources and applications based upon time, country, user-group and IP addresses
Endpoint Security	Validates the security posture of devices before granting access by performing Antivirus and Malware Scan of the devices, Windows Registry checks etc
Multi-Factor Authentication (MFA)	Enhances security by requiring additional verification factors, such as Email based OTP and TOTP, while accessing resources remotely
Split Tunneling	Configurable options for routing only specific traffic through the secure tunnel
Zero Trust Principles	Enforces strict verification of users and devices before granting access
Dual Stack Lite	Support for NAT 46 / 64 and DNS 46 / 64 with DNS Proxy
IP Address Management	Dynamic IP allocation from configurable network pools (IPv4/IPv6) with automated lease management
VPN Protocol & Encryption	Modern VPN protocol utilizing Noise protocol framework with Curve25519 for key exchange, ChaCha20 for encryption, Poly1305 for authentication, and BLAKE2s for hashing
Policy Rules	HTTP request interception with policy-based traffic filtering with comprehensive request logging at VPN authentication layer.